

The Vito panel van - overview

Body
Wheelbase

Compact
[3200 mm]

Long
[3200 mm]

Extra-long
[3430 mm]

Panel van with standard roof



Load volume [m ³]	4.65	5.19	5.68
Payload ¹⁾ [kg]	922-952/1092-1122 ²⁾	875-955/1045-1125 ²⁾	850-930/1020-1100 ²⁾
Perm. GVW [kg]	2770/2940 ²⁾	2770/2940 ²⁾	2770/2940 ²⁾

Panel van with high roof



Load volume [m ³]	-	6.49	-
Payload ¹⁾ [kg]	-	895-915/1045-1085 ²⁾	-
Perm. GVW [kg]	-	2770/2940 ²⁾	-

Dualiner with standard roof



Load capacity behind rear seat row [m ³]	2.63	3.16	3.65
Payload ¹⁾ [kg]	1028-1055 ²⁾	1000-1027 ²⁾	975-1000 ²⁾
Perm. GVW [kg]	2940 ²⁾	2940 ²⁾	2940 ²⁾

Dualiner with high roof



Load capacity behind rear seat row [m ³]	-	3.95	-
Payload ¹⁾ [kg]	-	987 ²⁾	-
Perm. GVW [kg]	-	2940 ²⁾	-

¹⁾Figure according to Directive 92/21/EC, version 95/48/EC for standard-specification vehicles. Optional equipment and accessories will generally increase this figure and reduce the payload capacity accordingly. The payload indicated for the Dualiner assumes that the rear seat row is not fitted

²⁾GVW can be uprated optionally by means of equipment code XA2